
# **CAD-CUT®** SILICONE 100

# DURABLE SILICONE MATERIAL WITH A MATTE FINISH AND A SOFT TOUCH.

The material is 100 microns thick, and is perfect for designs to be cut with medium to large detail. The material is stretchable and prevents dye migration on sublimated polyester.



(150°C 150°C 10 sec

100 MICRONS

#### AVAILABLE IN

50 cm x 25 m rolls

### RECOMMENDED FABRICS

- 100% Cotton
- 100% Polyester\*
- Polyester-Cotton blends
- Sublimated Polyester
- \* Test before application!

# CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least  $1.5 \text{ mm} (1/16^{\circ})$  for lettering and logos.

### APPLICATION INSTRUCTIONS

- Temperature: 150° C
- Time: 10 sec.
- Pressure: Medium (#4-6 on Hotronix<sup>®</sup>)
- Peel: Cold
- Repress: 5 sec.

# MULTI-COLOR DESIGNS

CAD-CUT® Silicone is not suitable for multi-layer applications.

#### ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®, LED Weeder. LED Pin or Tweezers

## CARE INSTRUCTIONS

Machine wash up to  $60^\circ\,\text{C}$  using mild detergent. Do not use bleach. Do not dry clean. Iron only inside out.

#### STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

#### DETAILS









# **CAD-CUT®** SILICONE 100

